# Data Sheet





# SCALEOVIEW H22-1W 22-inch LCD widescreen Display

Issue February 2007

Pages 2

Finally, there is the best choice display to show your data from all consumer electronic devices, like video/HD-DVD/BlueRay players, video recorders, SAT receivers and PCs. Sleek and space-saving it is a real eye-catcher in your room. Thanks to the new features incorporated in the DisplayView™ technology, it offers best performance for home office as well as a new experience for multimedia application such as photo editing and gaming.

#### **Highlights**

- n Best performance at an affordable price
  - Office applications
  - Internet and multimedia are supported best
- n Very easy and comfortable to use
  - Plug & Play
  - Auto-adjust
  - Easy-to-use OSD menu
  - Integrated Composite Video (AV) and S-Video interface

# DisplayView<sup>™</sup> technology

### n DisplayView™ Bright:

Color engine for optimized picture quality

#### n DisplayView™ Clean:

Tidy desk with

- Optimized cable conduct
- Integrated USB port for comfortable connection of digital camera or memorystick
- Integrated audio interface for comfortable connection of headset
- Integrated pen tray for storage of pens, post its, etc.

# n DisplayView™ Light:

Adjustable desk light above pen tray for better sight on your desk

#### **Ergonomics**

- n Optimum flicker-free and distortion-free ergonomics
- n Excellent color purity
- n Well balanced brightness uniformity
- n Excellent high contrast 2500:1 (dynamic contrast)
- n Space saving design fitting perfectly to the Fujitsu Siemens Computers SCALEO PCs
- n Fast response times 5ms

#### **Technical highlights**

n 22" (56 cm) widescreen LCD Display

n Excellent contrast 2500:1 (dynamic contrast)
n Brightness 300 cd/m² (typical)
n Response time 5 ms (typical)

n Response time 5 ms (typical)
n Viewing angle 160° / 160°
n Video interference 5 ms (typical)

n Video interfaces
 n Audio connectors
 n 2x USB connectors
 n DisplayView™ Light
 D-SUB, DVI, HDMI, Video, S-Video
 for microphone and headset
 for camera / memorystick
 adjustable desk light

#### Reliability

- **n** Low power consumption
- n Power management according EPA
- n Guaranteed quality and stability





Visible screen diagonal	22 inch (56 cm)
Resolutions	
Pixels	1680x 1050
Picture size	473.76 x 296.16 mm
Colors	16.7 million
Pixel Pitch	0.282 mm
Frequencies	
Horizontal	31 - 83 kHz
Vertical	50 - 75 Hz
Brightness (typical)	300 cd/m <sup>2</sup>
Contrast (dynamic)	2500:1
Viewing angle (typical)	
Horizontal	160°
Vertical	160°
Response time (typical)	5 ms
Plug and Play	VESA DDC2B
Setting options	

**Setting options** 

Power on/off, Auto Adjust, Brightness, Contrast, Clock, Phase, Sharpness, Color Control., OSD Position, OSD Time out, Factory recall, Information, Volume Control, Mode Control for different pictures, Desk light Control, Source Selection (Video or PC Mode)

**OSD Language** 

English, German, Spanish, French, Italian, Russian, Swedish, Dutch

Base Tilt angle	-5° / +20°	
Video input VGA, DVI, HDMI, Video, S	-Video	

Audio input/output
Audio signal input
Audio output / Max

3.5mm stereo phone jack
4 W (L) + 4 W (R)

Electrical values (external power adapter)

Rated voltage 100 - 240 V Frequency 47 - 63 Hz

Power draw

Max/Typ 60 W/ 50 W Stand by 2 W Protection class 1

Temperatures/ dimensions/ weight

Ambient temperature (to IEC721):

Working (recommended) 15°C to 32°C Storage -20°C to 60°C

Dimensions (H x W x D): 513.7 x 444.8 x 219.8 mm

(with stand)

Weight (Monitor only): 5.4 kg

Reliability

MTBF (demonstrated) 70,000 h Lifetime of LCD backlight 50,000 h (brightness > 50 % of original brightness)

**Compliance with standards** 

Product safety EN60950 Ergonomics GS mark

ISO13406-2 (Pixel fault class II)

Radiation immunity and CE certification according RFI suppression to EC Directive

to EC Directive 89/336/EEC

(EN55022/B, EN55024 EN61000-3-2/-3);

TCO'03

**Accessories** 

External power adapter
Power cable (1.8 m) For wall socket

(Euro-Schuko-Type CEE7)

Data cable (1.8 m)\* D-SUB (15-pin)

Data cable (1.8 m)\* DVI-D (24-pin)

Data cable (1.8 m)\* HDMI (19-pin)

USB cable (1.8m)\* USB-A to USB-B

Audio cable (1.8 m)\* 1x microphone, 1x speaker \* detachable on display

Special features

interface according VESA FPMPMI (100 mm) Kensington Lock adjustable blue desk light removable pen tray removable back cover

Standardized mounting

cable loop loop through USB connector loop through headset connector

 Order code
 S26361-K1118-V170

 EAN
 4045827723202





